High-Resolution
19” LCD KVM Switch
8 Port







FEATURES

- Front LCD Console (keyboard, mouse, monitor 19”) + 8ports KVM Module design; It’s very flexible and convenient for combination
- Keyboard is with demountable design, with 9 different languages: American, English, German, French, Spanish, Swiss, Turkish, Russian, Italian
- IP optional (IP card could be installed inside KVM module)
- The front USB design
- Cascade function support
- Total length: 611mm, fit for 800-1200mm cabinet
- Cable: 1.8/3/5m are available

Product Specification (19” LCD Console Specification)

Parameter		Specification
LCD Monitor	Type	18.51” Wide-Screen LCD Console
	Ratio	18.51” Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	409.8(H) x 230.4(V)
	Resolution	1366*768 @60HZ(Optimum)/1920*1080@60HZ(Max)
	Support Color	16.7M, True 8 bit
	Contrast	1000 : 1 (Typ)
	Back light	LED
	Pixel Pitch	300*300um
	LED MTBF	100,000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible	Microsoft Windows9, Me/NT/2000/XP, WIN7,
	IBM/AT	Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)

Litech®

High-Resolution
19” LCD KVM Switch
8 Port

Parameter		Specification
Mouse	Using life	>1,000,000 Times
Installation Dimension		407*445*45mm
Weight		6.07kg

Product Specification (KVM Module Specification)

Parameter			Specification
Model No. (Completed device)			LT1908
Computer Connection	Direct Connects		8
	Maximum Connects		128
CPU Port Selection			OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)
Connectors	Console Connector		DB 37PIN
	PC Connector	Monitor, Keyboard/Mouse Switch Module	8 x VGA DB15, Female Blue
	Power		1 x DC Jack
	Network Port		1 x RJ45(Optional)
Key Switch	Connection Port Selection		KVM Operation Panel Digital keys
	KVM Reset		KVM Operation Panel Function Keys
	IP Module Reset		1 x semi-embedded key
	IP Module Default		1 x semi-embedded key
LED’s	Selected		Nixie Tube Display
	Online		8 x Red
	IP Network		1 x Green, 1 x Orange
Analog Mode	Keyboard/Mouse		USB, PS/2
Resolution (Max)			1920 x 1200 @ 60HZ Local & Remote
Scan time interval			3, 5, 10, 15, 20, 30, 40, 60s (3s by default)
Operating Environment	Operating Temperature		-10-50˚C
	Storage Temperature		-20-60˚C
	Humidity		0-80%RH, No Condensation
Physical Properties	Housing		Metal
	Dimension		148.4*445*45mm
	Weight		3.32kg

Ordering Information

Part Number	Product Description
LTR-KVM-LCD-8P	High-Resolution 19” LCD KVM Switch 8 Port

Litech®